



LPV™

ELECTRIC LOW PROFILE V-BOX SPREADER



NEW
PRODUCT

GO LOW & SPREAD QUIETLY!

Performance and Productivity

Advantages are standard

on Swenson's new

Low Profile PV Spreader!

*THE NEW SWENSON ELECTRIC LPV
ELIMINATES COMMON MAINTENANCE
ISSUES SUCH AS CLUTCHES, SPARK
PLUGS, CARBURETORS AND MANY
OTHER MAINTENANCE ITEMS.

WWW.SWENSONSPREADER.COM

swenson  **spreader**

GO LOW & SPREAD QUIETLY!



PRODUCTIVITY ADVANTAGE

The 12V electric motor driven LPV has fewer parts, which means less maintenance and less downtime

PERFORMANCE ADVANTAGE

The electric motor means you can spread salt without the noise and annoyance of most gas engines

COMPETITIVE ADVANTAGE

The LPV's electric motor draws less battery current than competitive electric spreaders thus providing less wear and tear on your electrical system

SAFETY ADVANTAGE

The lower height of the spreader provides increased rearward visibility



Contact your local distributor to see how you can "Go Low & Spread Quietly!"

WWW.SWENSONSPREADER.COM

LPV™

ELECTRIC LOW PROFILE V-BOX SPREADER

THE NEW ELECTRIC POWERED LPV SPREADER HAS AN OVERALL HEIGHT 25% LESS THAN TYPICAL PICKUP TRUCK SPREADERS

Swenson Spreader, the leader in spreader equipment and technology, introduces the new Electric Powered LPV Spreader (Low Profile V-box). This unit is specifically designed for 1/2 ton to 1-ton pickups* and since the overall height is 25% less than typical pickup truck spreaders, rearward visibility is significantly increased. And because it's a Swenson, you know it's reliable and has outstanding performance. The LPV has been developed with field-operators and field-tested to be the quietest and most efficient electric powered spreader available. The LPV is powered by a sealed, 12V electric motor and has fewer parts, which means less maintenance and less downtime. This quiet operator means business – safe, profitable and productive business for you.

General Specifications

- Spreads free flowing materials – sand and/or salt
- Spread widths of 4' to 20'
- Includes top screens
- Powder coated in Swenson Safety Yellow

Hopper

- Durable construction: double crimped top edges and four (4) body supports
- 45 degree sides allow free flow of materials to conveyor

Conveyor

- Drag chain ensures constant flow of materials
- 12" wide conveyor
- Replaceable conveyor floor and chain shield

Spinner Assembly

- 13" Poly spinner disc with molded flites
- 2 internal and 4 external baffles provide precise material spreading
- Overlapping baffles for improved control at narrow spread width

Power Supply

- Sealed 12V electric motor
- Gas engine available

DIMENSIONS & CAPACITIES

Size Available:	5 to 8 feet	Hopper Width:	36 inches
Capacity By Weight:	1134 to 1924 lbs.	Conveyor Width:	12 inches
Capacity By Size:	0.56 to 1.39 cu. yds.	Unit Weight Empty:	472 to 586 lbs.
Overall Length:	80 to 116 inches	Unit Weight Loaded:	1600 to 3300 lbs.*
Hopper Length:	60 to 96 inches	Spread Pattern:	4 to 20 feet
Hopper Height:	25 inches		

*Never exceed the load capacity of your truck. Check your owners manual.

swenson spreader

SWENSON SPREADER LLC
PO BOX 127 • LINDENWOOD, ILLINOIS 61049
888.825.7323 • FAX 866.310.0300
swensonsales@swensonspreader.com

Swenson Spreader reserves the right under its continuing product improvement program, to change construction or design details and specifications without notice or without incurring any obligation.